



uni  
KENDrill

Broca de metal duro integral, serie extra larga 30xD, con refrigeración interna  
*Solid carbide twist drill, extra long serie 30xD, with internal cooling*  
Foret en carbure monobloc, série extra longue 30xD, avec trous de lubrification  
*Punta en metallo duro, serie extra lunga 30xD, con canali di refrigerazione*  
Hochleistungsbohrer VHM mit Innenkühlun, extra lang, Ausführung 30xD  
*Цельные твердосплавные сверла, экстра длинная серия 30xD, с внутренним подводом СОЖ*

R230.6D

K  
DRILL

30xD

KENDU  
NORM

DIN  
6535-HA

30°  
HELIX

Pilot

D

D

HM  
MG 10

N  
TYP

DIN  
6535-HA

30°  
135°

Pilot

D

D

D	d	l	L	L4	R230.6D.
h7	h6				
3	6	100	140	36	00300
3,5	6	136	176	36	00350
4	6	136	176	36	00400
4,5	6	168	208	36	00450
5	6	168	208	36	00500
5,5	6	200	240	36	00550
6	6	200	240	36	00600
7	8	232	272	36	00700
8	8	263	303	36	00800
9	10	295	339	40	00900
10	10	327	371	40	01000

Condiciones de corte  
*Cutting conditions*  
Conditions de coupe  
*Condizioni di taglio*  
Schnittbedingungen  
*Режимы резания*

R230.6D										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 5÷50 HRc	Acero Steel 50÷70 HRc
😊	🎯	😊							🎯	

[illegible]





