



uni
KenGraf



HM
MG 6

R ±0,02

KENDU
NORM


SERIE
L

N
TYP

HSC


30°
HELIX

DIN
6535-HA



Fresa frontal punta semiesférica, 4 labios, larga
4 flute ball nose end mill, long
Fraise cylindrique à bout hémisphérique, 4 dents, longue
Fresa cilindriche frontali a testa semisferica, 4 denti, lunga
Kugelfräser, 4 Schneiden, lang
Фреза 4-х зубая с полусферическим торцом, длинная

D	d	I	L	Z	R	2901.26.
h9	h6				±0,02	
4	4	30	100	4	2	00400
5	5	35	100	4	2,5	00500
6	6	40	100	4	3	00600
8	8	45	100	4	4	00800
10	10	45	100	4	5	01000
12	12	45	100	4	6	01200



Condiciones de corte
Cutting conditions
Conditions de coupe
Condizioni di taglio
Schnittbedingungen
Режимы резания

2901.26										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 45÷50 HRc	Acero Steel 50÷70 HRc
						😊				

