






Steelken




DIN 845-B NORM
DIN 228-A
Brillante Uncoated



Fresa frontal de gran desbaste, varios labios - Cono Morse
Several flute roughing end mill - Morse taper
Fraise cylindrique ravageuse en bout, multident - Cône Morse
Fresa cilindriche frontali per sgrossatura, multident - Cono Morse
Schrupp-Mehrzahlfräser - Morsekegel
Фреза многозубая черновая, хвостовик с конусом Морзе

D	CM	I	L	Z	216.80.
k12					
14	2	26	111	4	01400
15	2	26	111	4	01500
16	2	32	117	4	01600
18	2	32	117	4	01800
20	2	38	123	4	02000
22	2	38	123	5	02200
24	3	45	147	5	02400
25	3	45	147	5	02500
26	3	45	147	5	02600
28	3	45	147	5	02800
30	3	45	147	5	03000
32	4	53	178	6	03200
34	4	53	178	6	03400
36	4	53	178	6	03600
38	4	63	188	6	03800
40	4	63	188	6	04000
45	4	63	188	6	04500
50	5	75	233	8	05000
63	5	90	248	8	06300



Condiciones de corte
Cutting conditions
Conditions de coupe
Condizioni di taglio
Schnittbedingungen
Режимы резания

216.80										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 45÷50 HRc	Acero Steel 50÷70 HRc
😊	😊	😊		😊			😊	😊		

