



Steelken

232.80

232.81

Brillante  
Uncoated


K  
PLUS

HSSE  
Co 8

DIN  
1880  
NORM


N  
TYP

30°  
HELIX



Fresa frontal con ranura transversal  
*Shell mill with cross slot*  
Fraise trou lisse avec rainure trasversale  
*Fresa frontali con cava trasversale*  
Walzenstirfräser mit Quernute  
*Фреза торцово-цилиндрическая*

D	d	A	Z	232.80.	232.81.
k10	H7				
40	16	32	6	04000	04000
50	22	36	8	05000	05000
63	27	40	8	06300	06300
80	27	45	10	08000	08000
100	32	50	12	10000	10000



Condiciones de corte  
*Cutting conditions*  
Conditions de coupe  
*Condizioni di taglio*  
Schnittbedingungen  
*Режимы резания*

232.80										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 45÷50 HRc	Acero Steel 50÷70 HRc
😊	😊	😊		😊			😊	😊		

232.81										
Acero Steel <1400 N/mm²	Inox Stainless	Fundición Cast iron	ALU Mg	Cu	Materiales sintéticos Fiber	Grafito Graphite	Ti	Ni	Acero Steel 45÷50 HRc	Acero Steel 50÷70 HRc
😊	😊	😊		😊			😊	😊		







[illegible]











[illegible]

[illegible]



[illegible]