



uni
KenGraf



HM
MG 6

KENDU
NORM


SERIE
XL

N
TYP

HSC


30°
HELIX

DIN
6535-HA



Fresa frontal, 4 labios, con radio en la esquina, extra larga - Corte al centro
4 flute corner radius end mill, extra long - Center cut
Fraise cylindrique en bout, 4 dents, avec rayon d'angle, extra longue - Coupe au centre
Fresa cilindriche frontali, 4 denti, con raggio di spigolo, extra lunga - Taglio al centro
Langlochfräser, 4 Schneiden, mit Eckenradius, extra lang - Zentrumsschnitt
Фреза 4-х зубая концевая с радиусами при вершине, экстрадлинная серия

| D | d | I | L | Z | D3 | L3 | R | |
|-----|----|----|-----|---|------|-----|-------|------------------|
| h10 | h6 | | | | | | ±0,02 | 2203.26. |
| 6 | 6 | 50 | 150 | 4 | 5,8 | 100 | 0,3 | 00600 |
| 8 | 8 | 50 | 150 | 4 | 7,7 | 100 | 0,5 | 00800 |
| 8 | 8 | 15 | 150 | 4 | 7,7 | 60 | 0,3 | 008006003 |
| 10 | 10 | 60 | 150 | 4 | 9,7 | 100 | 0,5 | 01000 |
| 12 | 12 | 60 | 150 | 4 | 11,7 | 100 | 0,5 | 01200 |



Condiciones de corte
Cutting conditions
Conditions de coupe
Condizioni di taglio
Schnittbedingungen
Режимы резания

| 2203.26 | | | | | | | | | | |
|-------------------------------|-------------------|------------------------|-----------|----|-----------------------------------|---------------------|----|----|-----------------------------|-----------------------------|
| Acero Steel <1400 N/mm² | Inox Stainless | Fundición Cast iron | ALU Mg | Cu | Materiales sintéticos Fiber | Grafito Graphite | Ti | Ni | Acero Steel 45÷50 HRc | Acero Steel 50÷70 HRc |
| | | | | | | 😊 | | | | |

